


4000, 3000, 2000 SERIES ANSI GRADE 2

GRADE 2

Factory tested to meet ANSI Grade 2 durability



10-Year Warranty



Model

4000 Standard power size 4 3000 Standard power size 3 2000 Standard power size 2

Applications

- Medium and Light Duty model Medium Duty 4000 Light Duty 3000, 2000
- Universal mounting hole pattern Size 4: CTC 9-1/16" x 3/4" Size 3: CTC 8-3/16" x 3/4" Size 2: CTC 6-5/8" x 3/4"




Product Specification Aluminum alloy body, forged steel arm Material Heat treated forged steel piston Double Heat treated Steel pinion Valves Dual valves control for Closing speed and Latching speed. Standard arm and parallel bracket included for different Arm & mounting demand **Brackets** Screws Wood screws and machine screws Finishes Aluminum, Duronotic, and Gold

Optional Fuctions

- Hold Open Arm (3001, 4001)
- Drop Plate (See Accessories)
- Sex-bolts (Metal door mounting)
- Full plastic cover, available for 4000 series only (40C)

Technical Dimensions			
Series 4000, 3000, 2000	Size		
A. Length of Closer Body	9-3/4"	8-3/4"	7-5/16"
B. Horizontal Mounting Holes	9-1/16"	8-3/16"	6-5/8"
C. Vertical Mounting Holes	3/4"	3/4"	3/4"
D. Height of Closer Body	1-3/4"	1-3/4"	1-3/4"
E. Projection from Door	2-7/8"	2-7/8"	2-5/8"



Accessories

4001

Hold-open Arm For 4000 Series Pull side and top jamb

Use with PA bracket for parallel arm mount

HFW01 Flat Wrench For Hold Open Arm




Parallel Bracket for Hold Open Arm mounting can also use for regular parallel arm application

3001 Hold-open Arm For 3000 Series





Sex-bolt with screw For 1-3/4" standard Door Thick



40DP-PA For 4000 Series Size: 9-3/4" x 3-1/2"

40DP-TJ For 4000 Series

Size: 9-3/4" x 2-9/16"

Drop Plate -Parallel arm mount

Used to mount a closer on a top rail as narrow as 2-5/8" in height 30DP-PA For 3000 Series

Size: 3-1/2" x 8-3/4" Drop Plate - Parallel arm mount 20DP-PA For 2000 Series

0 Size: 3-1/2" x 7-5/16" Drop Plate - Parallel arm mount



